

## 15A, 600V - 1000V Standard Bridge Rectifier

### FEATURES

- Ideal for printed circuit board
- High surge current capability
- UL Recognized File # E-326243
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21


### APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- TV
- Monitor


### MECHANICAL DATA

- Case: GBU
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1 whisker test
- Polarity: As marked
- Weight: 3.96g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_F$	15	A
$V_{RRM}$	600 - 1000	V
$I_{FSM}$	220	A
$T_{J\ MAX}$	150	°C
Package	GBU	
Configuration	Quad	



GBU



ABSOLUTE MAXIMUM RATINGS (T <sub>A</sub> = 25°C unless otherwise noted)						
PARAMETER		SYMBOL	GBU1505	GBU1506	GBU1507	UNIT
Marking code on the device			GBU1505	GBU1506	GBU1507	
Repetitive peak reverse voltage		V <sub>RRM</sub>	600	800	1000	V
Reverse voltage, total rms value		V <sub>R(RMS)</sub>	420	560	700	V
Forward current		I <sub>F</sub>	15			A
Surge peak forward current single half sine-wave superimposed on rated load per diode	t = 8.3ms	I <sub>FSM</sub>	220			A
	t = 1.0ms		600			
Rating of fusing ( t<8.3ms)		I <sup>2</sup> t	200			A <sup>2</sup> s
Junction temperature		T <sub>J</sub>	- 55 to +150			°C
Storage temperature		T <sub>STG</sub>	- 55 to +150			°C

**THERMAL PERFORMANCE**

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance	$R_{\theta JL}$	1.5	°C/W
Junction-to-ambient thermal resistance	$R_{\theta JA}$	7.5	°C/W
Junction-to-case thermal resistance	$R_{\theta JC}$	1.0	°C/W

**Thermal Performance Note:** Mounted on Heat sink with 4" x 6" x 0.25" Al -Plate.

**ELECTRICAL SPECIFICATIONS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode <sup>(1)</sup>	$I_F = 7.5\text{A}, T_J = 25^\circ\text{C}$	$V_F$	0.93	-	V
	$I_F = 15\text{A}, T_J = 25^\circ\text{C}$		1.00	1.10	V
	$I_F = 7.5\text{A}, T_J = 125^\circ\text{C}$		0.82	-	V
	$I_F = 15\text{A}, T_J = 125^\circ\text{C}$		0.92	-	V
Reverse current @ rated $V_R$ per diode <sup>(2)</sup>	$T_J = 25^\circ\text{C}$	$I_R$	-	5	$\mu\text{A}$
	$T_J = 125^\circ\text{C}$		-	500	$\mu\text{A}$
Junction capacitance per diode	1MHz, $V_R = 4.0\text{V}$	$C_J$	79	-	pF

**Notes:**

1. Pulse test with  $PW = 0.3\text{ms}$
2. Pulse test with  $PW = 30\text{ms}$

**ORDERING INFORMATION**

ORDERING CODE <sup>(1)</sup>	PACKAGE	PACKING
GBU150x	GBU	20 / Tube


**Notes:**

1. "x" defines voltage from 600V(GBU1505) to 1000V(GBU1507)


## CHARACTERISTICS CURVES

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Junction Capacitance**




**Fig.3 Typical Reverse Characteristics**



**Fig.4 Typical Forward Characteristics**



## PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	3.30	3.56	0.130	0.140
A2	2.40	2.66	0.094	0.105
b	1.02	1.27	0.040	0.050
b2	2.06	2.54	0.081	0.100
c	0.46	0.56	0.018	0.022
D	18.30	18.80	0.720	0.740
D1	7.40	7.90	0.291	0.311
D2	1.65	2.16	0.065	0.085
E	21.80	22.30	0.858	0.878
E1	3.50	4.10	0.138	0.161
e	4.83	5.33	0.190	0.210
L	17.50	18.00	0.689	0.709
L4	1.91	2.54	0.075	0.100

## MARKING DIAGRAM



P/N = Marking Code  
G = Green Compound  
YWW = Date Code  
F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[GBU1506](#) [GBU1507](#) [GBU1505](#)