

## Specification Sheet

Part Number: MB4SHA10H4



For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb.

A predrilled hole extends mounting options and solutions.

Extended adhesive liner is easy to remove quickly.

Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg

|                |           |
|----------------|-----------|
| Article Number | 151-29206 |
|----------------|-----------|

|      |        |
|------|--------|
| Type | MB4SHA |
|------|--------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |     |
|--------------|-----|
| Quantity Per | bag |
|--------------|-----|

|                     |                                                                                                                                                                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | MB4SHA adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have a predrilled hole to extend mounting options. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------|
| Short Description | Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 500/pkg |
|-------------------|--------------------------------------------------------------------------------------------------|

|                  |                |
|------------------|----------------|
| Global Part Name | MB4SHA-PA66-WH |
|------------------|----------------|

|                                       |                             |
|---------------------------------------|-----------------------------|
| Length L (Imperial)                   | 1.12                        |
| Length L (Metric)                     | 28.3                        |
| Fixation Method                       | Screw Mounting and Adhesive |
| Width W (Imperial)                    | 1.12                        |
| Width W (Metric)                      | 28.3                        |
| Cable Ties                            | T18 - T50                   |
| Height H (Imperial)                   | .23                         |
| Height H (Metric)                     | 5.8                         |
| Cable Tie Width Max (Imperial)        | 0.18                        |
| Cable Tie Width Max (Metric)          | 4.6                         |
| Mounting Hole Diameter D (Imperial)   | 0.15                        |
| Mounting Hole Diameter D (Metric)     | 3.9 mm                      |
| Mounting Hole Diameter D Max (Metric) | 3.9                         |
| Material                              | Polyamide 6.6 (PA66)        |
| Material Shortcut                     | PA66                        |

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Adhesive                       | Synthetic rubber with base of polyethylene foam |
| Flammability                   | UL 94 V-2 (excluding adhesive)                  |
| UV Resistant (Yes/No)          | No                                              |
| Adhesive Operating Temperature | 0°F to +150°F (-18 °C to +66 °C)                |
| Operating Temperature          | -40°F to +185°F (-40°C to +85°C)                |
| Reach Compliant (Article 33)   | No                                              |
| ROHS Compliant                 | Yes                                             |
| Package Quantity (Imperial)    | 500                                             |
| Package Quantity (Metric)      | 500                                             |
| Customs Number                 | 3926909988                                      |

### About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).