

- Compact metal case with screw terminal block
- Universal input 85-264 VAC
- High efficiency up to 91%
- Active PFC >0.95
- Compliance to EN 61000-3-2
- Short circuit, overvoltage and overload protection
- IEC/EN/UL 62368-1 safety approvals
- Remote On/Off and Remote Sense
- 3 year product warranty



The TXLN series is a family of encased power supplies designed for a wide range of cost critical applications. With a low profile metal case and screw terminal block connection, they are easy to install in any equipment. These power supplies have universal input and comply with European EMC standards and the Low Voltage Directive (LVD).

Models

Order Code	Output Power max.	Output Voltage nom. (adjustable)	Output Current max.	Efficiency typ.
TXLN 500-112	500 W	12 VDC (10.8 - 13.2 VDC)	41'700 mA	88 %
TXLN 500-124		24 VDC (21.6 - 26.4 VDC)	21'000 mA	89 %
TXLN 500-148		48 VDC (43.2 - 52.8 VDC)	10'500 mA	91 %

Options

on demand (backorder with MOQ non stocking item)	- Optional model with 5 VDC / 90'000 mA - Optional model with 36 VDC / 14'000 mA
---	---

Input Specifications

Input Voltage	- AC Range	Operational Range: 85 - 264 VAC (Full Range) Rated Range: 100 - 240 VAC (Full Range)
	- DC Range	Operational Range: 120 - 375 VDC (Designed for, no certification) Polarity: irrelevant
Input Frequency		Operational Range: 47 - 63 Hz Certified: 50/60 Hz
Input Current	- Full Load & Vin = 115 VAC	6'600 mA max.
Input Inrush Current	- At 230 VAC	40 A max.
	- At 115 VAC	20 A max.
Power Factor	- At 230 VAC	0.95 min. (Active Power Factor Correction)
	- At 115 VAC	0.95 min. (Active Power Factor Correction)
Input Protection		T 10 A / 250 VAC (Internal Fuse)
Recommended Input Fuse		10'000 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)

Output Specifications

Output Voltage Adjustment		±10% (By trim potentiometer) Output power must not exceed rated power!
Voltage Set Accuracy		±2% max. (5 Vout model) ±1% max. (other models)
Regulation	- Input Variation (Vmin - Vmax)	1% max. (5 Vout model) 0.5% max. (other models)
	- Load Variation (0 - 100%)	2% max. (5 Vout model) 1% max. (other models)
Ripple and Noise (20 MHz Bandwidth)	5 VDC model:	150 mVp-p max. (w/ 0.1 µF // 47 µF)
	12 VDC model:	150 mVp-p max. (w/ 0.1 µF // 47 µF)
	24 VDC model:	150 mVp-p max. (w/ 0.1 µF // 47 µF)
	36 VDC model:	200 mVp-p max. (w/ 0.1 µF // 47 µF)
	48 VDC model:	200 mVp-p max. (w/ 0.1 µF // 47 µF)
Minimum Load		Not required
Temperature Coefficient		±0.03 %/K max.
Hold-up Time	- At 230 VAC	18 ms min.
	- At 115 VAC	18 ms min.
Start-up Time	- At 230 VAC	3'000 ms max.
	- At 115 VAC	3'000 ms max.
Short Circuit Protection		Continuous, Automatic recovery
Output Current Limitation		105 - 130% of Iout max.
Overvoltage Protection		115 - 140% of Vout nom.

Safety Specifications

Safety Standards	- IT / Multimedia Equipment	EN 62368-1 IEC 62368-1 UL 62368-1
	- Certification Documents	www.tracopower.com/overview/txln500
Protection Class		Class I (Prepared): Connection to PE
Pollution Degree		PD 2
Over Voltage Category		OVC II

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

EMC Specifications

EMI Emissions	- Conducted Emissions - Radiated Emissions - Harmonic Current Emissions - Voltage Fluctuations & Flicker	EN 55032 class B (internal filter) EN 55032 class B (internal filter) EN 61000-3-2, class D EN 61000-3-3
EMS Immunity	- Electrostatic Discharge - RF Electromagnetic Field - EFT (Burst) / Surge - Conducted RF Disturbances - PF Magnetic Field - Voltage Dips & Interruptions	EN 55024 (IT Equipment) Air: EN 61000-4-2, ± 8 kV, perf. criteria A Contact: EN 61000-4-2, ± 4 kV, perf. criteria A EN 61000-4-3, 3 V/m, perf. criteria A EN 61000-4-4, ± 1 kV, perf. criteria A L to L: EN 61000-4-5, ± 1 kV, perf. criteria B L to PE: EN 61000-4-5, ± 2 kV, perf. criteria B EN 61000-4-6, 3 Vrms, perf. criteria A Continuous: EN 61000-4-8, 3 A/m, perf. criteria A 230 VAC / 50 Hz: EN 61000-4-11 30%, 25 periods, perf. criteria A >95%, 0.5 periods, perf. criteria A >95%, 250 periods, perf. criteria B

General Specifications

Relative Humidity	90% max. (non condensing)
Temperature Ranges	- Operating Temperature - Storage Temperature -30°C to +70°C -40°C to +85°C
Power Derating	- High Temperature - Low Input Voltage 2.5 %/K above 50°C 0.7 %/V below 100 VAC
Over Temperature Protection Switch Off	Latch off
Cooling System	Forced air cooling (with internal fan)
Fan Power Source	- Characteristic - Output Voltage - Output Current Variable fan speed (temperature regulated) 12 VDC 92 mA max.
Remote Control	- Voltage Controlled Remote On: 0 to 0.8 VDC Off: 4 to 10 VDC Refers to '+Remote' and '-Remote' Pin
Altitude During Operation	5'000 m max. (The max. ambient temperature decreases by 5 K / 1000 m when operated above 2000 m)
Switching Frequency	60 - 80 kHz (PWM)
Insulation System	Reinforced Insulation
Isolation Test Voltage	- Input to Output, 60 s - Input to Case or PE, 60 s - Output to Case or PE, 60 s 3'000 VAC 1'800 VAC 500 VAC
Isolation Resistance	- Input to Output, 500 VDC 100 M Ω min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V 4'700 pF max.
Leakage Current (at 264 VAC / 60Hz)	- Earth Leakage Current 1500 μ A max.
Reliability	- Calculated MTBF 138'700 h (MIL-HDBK-217F, ground benign)
Housing Material	Aluminum
Housing Type	Metal Case
Mounting Type	Chassis Mount
Connection Type	Screw Terminal
Weight	1'110 g
Status Indicator	Indicated by green LED
Sense Function	(to be done)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Environmental Compliance - REACH Declaration

- RoHS Declaration

www.tracopower.com/info/reach-declaration.pdf

REACH SVHC list compliant

REACH Annex XVII compliant

www.tracopower.com/info/rohs-declaration.pdf

Exemptions: 7a, 7c-I

(RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).


The SCIP number is provided on request.)

Supporting Documents

[Overview Link](#) (for additional Documents)

www.tracopower.com/overview/txln500

Outline Dimensions



Dimensions in mm
Tolerances:
0-8: ± 0.2
8-25: ± 0.3
25-80: ± 0.5
80-250: ± 0.8

Mounting screws
Max. screw penetration depth: 5.0
Max. screw locked torque: 0.8 Nm

Input	
CN1	
Pin	Function
1	AC (L)
2	AC (N)
3	PE

Output	
CN3	
Pin	Function
1-3	-Vout
4-6	+Vout

Auxiliary	
CN2	
Pin	Function
1	-Remote
2	-Sense
3	+Remote
4	+Sense

CN1:
3 pin, 9.5mm pitch
with PC cover


CN3:
6 pin, 11 mm pitch

CN2 Housing Type:
HRS DF11-04DP-2DS

CN2 Mating Housing:
HRS DF11-4DS

CN2 Crimp Contact:
HRS DF11-**SC

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Mounting Bracket (included)


Dimensions in mm

Included in shipment:
 - 4x Mounting Bracket
 - 4x M4 mounting screw

